

**Features:**

- Wall mounting
- IP65 (dust tight & water jet proof)
- High performance energy efficient Osram surface-mount-device (SMD) LEDs
- Available in 4000K (cool white)
- Average 50,000 hrs LED life - L70 B10
- Visor for control of light pollution
- BESA box provision
- Removable gear tray

**Options:**

- Integral 3hr maintained emergency
- Integral photocell
- PRO ECO® (wireless testing & control system) available - on special request
- Tamper resistant Torx screws
- 3000K (warm white) LED colour temperature available - on special request

**Material:**

- Body: die-cast aluminium
- Lens: polycarbonate

**Finish:**


- Lens: cloud (standard) or prismatic (on special request)

**Colour:**


- 01 White (on special request, minimum order quantities may apply)
- 02 Black
- 03 Metallic Grey



**Technical**



**Photometrics**



Merlin					Ordering Code	
Wattage	Colour Temperature	LED Lumens	Delivered Lumens	Luminous Efficacy	Black	Metallic Grey
15W LED	4000K	2695lm	1751lm	117lm/W	65-181-060-402	65-181-060-403
16W LED	4000K	3250lm	2080lm	130lm/W	65-182-060-402	65-182-060-403
24W LED	4000K	4511lm	2932lm	122lm/W	65-183-060-402	65-183-060-403
Options					Add to Ordering Code	
Emergency (3 hour)  excludes 24W version					E3-	
Integral photocell					/P	
Torx screws					/TS	

