

### Features:

- Robust aluminium body
- Wall or ceiling mounting
- IP65 (dust tight & water jet proof)
- IK10 (20 joule) shock resistance
- High performance energy efficient Osram surface-mount-device (SMD) LEDs
- Available in 4000K (cool white)
- Average 50,000 hrs LED life - L70 B10
- BESA box provision
- 2x 20mm conduit entry for side wiring
- Removable gear tray

### Options:

- Integral 3hr maintained emergency
- Available with an integrated Manual Intelligent Control (MIC<sup>®</sup>) - not recommended for exterior use
- PRO ECO (wireless testing & control system) available - on special request
- Integral photocell
- Tamper resistant Torx screws
- 3000K (warm white) LED colour temperature available - on special request

### Material:

- Body: die-cast aluminium
- Lens: polycarbonate

### Finish:

- Lens: cloud (standard) or prismatic (on special request)


### Colour:

- 01 White
- 02 Black




AMENITY

### Technical



### Photometrics



Kite-R					Ordering Code	
Wattage	Colour Temperature	LED Lumens	Delivered Lumens	Luminous Efficacy	White	Black
15W LED	4000K	2695lm	2126lm	142lm/W	65-151-061-401	65-151-061-402
19W LED	4000K	3666lm	2896lm	152lm/W	65-152-061-401	65-152-061-402
28W LED	4000K	4948lm	3908lm	140lm/W	65-152-061-401	65-153-061-402

Options	Add to Ordering Code
Emergency (3 hour)  excludes 28W version	E3-
MIC 1	/MIC1
MIC 2	/MIC2
MIC 3	/MIC3
Integral photocell	/P
Torx screws	/TS

